



---

## Outdoor HD 30M IR Range Fixed Lens IP Camera



---

### Features

- Outdoor Bullet Camera
- IR cut filter for day/night operations
- IP66 rain and dust resistant
- 30-meter infrared night vision
- 1080p resolution @ 15fps

---

### Description

The L series cameras are your economical choice for small and medium sized businesses. LR832 Outdoor rated HD 30M IR Range Fixed Lens IP Camera in the L series is featuring 1080P at 15fps, built-in Sense up+ technology to deliver stunning video in low-light conditions. Utilising intelligent image signal processing, 2D WDR function, AGC control, and 3D Noise Reduction, the combination successfully delivers the ultimate low-light image without motion blur. The IP66-rated housing is designed to help the camera body withstand rain and dust and ensures operation under a multitude of harsh weather conditions. Support with PoE, privacy mask, White balance, and minimum illumination 0.15 Lux at F2.0 Low Light Mode

## Specifications

Model	LR832
Image Sensor/Sensor type	1/2.7" CMOS image sensor
Max. Image Pixels/ Total sensor pixels/ Effective Pixels	1920 (H) × 1080 (V) = 2,073,600 (pixel)
Video Compression	H.264 , Motion JPEG
Megapixels	1080P(1920 x 1080) , 720p(1280 x 720) , D1(720 x 480) , CIF(352 x 240)
Frame Rates	H.264 : up to 15 fps @ 1920 x 1080 , 30fps @ 1280 x 720 , 30fps @ 720 x 480 / Motion JPEG : up to 15 fps @ 1920 x 1080 , 30 fps @ 720 x 480 , 30 fps @ 352 x 240
Lens/Focal length	4mm
Iris	F2.0
Angle of View	94°(H), 50°(V), 102°(D)
IR Radiant Distance	30m
Infrared LED Angle	60° , 90°
Digital zoom	Yes
Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast
Video bitrate	128Kbps□8Mbps ; Frame rate and bitrate controllable on-the-fly ; VBR / CBR / GOP supported
Peak wavelength	850nm
Window / Glass Thickness	Ø58 Heat Resistant Glass
Scanning System	Progressive scan
IR cut filter	Colour (Day), Monochrome (Night), Auto, Schedule
Min. illumination/Low Light Mode (Colour)	Colour: 0.15 Lux at F2.0, B/W: 0.05 Lux at F2.0 , With Infrared LED 0.0 lux
White Balance	Auto / Tungsten / Indoor / Fluorescents1 / Fluorescents2 / Outdoor1 / Outdoor2
Back Light Compensation (BLC)	On / Off

Shutter Time	1/30(1/25)s to 1/8000s
Sense Up	Off / 1 frame / 2 frames / 3 frames / 7 frames
Sense Up+	Yes
Auto Gain Control	36 dB variable gain
3D Noise Reduction	Off / 1 to 32 selectable
2D WDR	Off / Auto / x2 / x3 / x4
Privacy Masking	Off / On (4 independent areas)
D/N quality setting	Yes
Adjustable picture setting	Contrast, Brightness, Saturation
Other functions	Sharpness, Image flip, Image mirror, Hue
Encryption	Base64 HTTP encryption
Access	Multiple user access levels with password protection
User accounts	10 user accounts available
IP address filter	Yes
Multi IP address	Yes
Users	8 simultaneous users
ePTZ & Digital Zoom	Yes
OSD (On-Screen Display)	Text overlay for date, time and camera name
Alarm event triggers	Motion detection triggering recording into SD card, Image upload over FTP and E-mail by motion detection
Alarm event actions	Yes
Alarm weighted mode	Yes
CPU	Embedded SoC ARM11, 528MHz, 256MB DDR2, 256MB flash memory
Firmware	Firmware upgrade via HTTP
Network Interface/Ethernet	10Mbps / 100Mbps Base-T, RJ-45
CE	Yes
FCC	Yes
Connectivity	ONVIF Profile S

OS requirement	Windows 2000, Windows XP, Windows Vista, Windows 7, Windows 8
Web browser	Microsoft® Internet Explorer® 6.0 and later
CPU requirement	Intel Pentium 4 1.8GHz or above
RAM requirement	1GB or above, Independent Display Card
Protocols	IPv4□IPv6□TCP□UDP□HTTP□SMTP□NTP□ DDNS□UPnP□FTP□ARP□DHCP□PPPoE□DNS□ RTSP□RTCP□Telnet□ICMP□IGMP□ONVIF Profile S□SNMP□SIP□Bonjour
RTSP Authentication	On / Off
Mobile phone	Integrated to LILIN mobile app (LILINViewer) ; iPhone, iPad, Android support
Video Management	ONVIF Profile S / LILIN Navigator Enterprise 1.0 / Third party VMS through LILIN HTTP API
Video Display	LILIN Universal ActiveX & LILIN Java Applet
OS	Embedded Linux 2.6.32
SD Card (recording)	Support Micro SD/SDHC card for circular recording (card is not included)
IP Rating	IP66 waterproof
Operating temperature	-40□ to 50□ (-40□ to 122□)
Dimensions	68mm x 69mm x 185mm
Weight	450g approx.
Power Supply	DC12V ±10%□Power over Ethernet (IEEE 802.3af compliant)
PoE	PoE , IEEE 802.3af
Power Consumption	DC12V, 7.5W / PoE, 8.5W